

KSEALCORE SL

SOLVENTED HIGH BUILD PROTECTIVE & DECORATIVE COATING FOR CONCRETE FLOORS & WALLS

BENEFITS

- Easily applied on dry or damp surfaces.
- Can be used on steel, galvanized steel substrates.
- Excellent protective properties.
- Minimum surface preparation required for rusted steel.
- Excellent over coating characteristics.
- Available in different colours.
- Can be applied on floors and walls.
- Easily applied on dry or damp surfaces.

PRODUCT

KSEALCORE SL is a two pack, high build, solvented epoxy Coating for, steel and concrete structures to provide protection from weathering and abrasion.

USE

To protect steel surfaces surface to enhanced resistance to oil, grease, water penetration, abrasion and chemical attack.

PROPERTIES

Colours : Blue, Grey, Red, Green (Special colours on order)

Pot Life At 30°C : 2 hours,

Curing At 30°C : 1 hours,

Touch Dry : 7 hours;

Full Cure: 7 days :

Temperature Range : During application,

5°C to 45°C In Service : Max. 70°C,

DFT : 300 micron/two coats.

PACKING & COVERAGE

5 Kg pack will cover an area of approximately 10-11 m² for recommended two coats.

SHELF LIFE

Shelf life is 12 months, when stored in manufacturer's undamaged sealed containers under dry conditions, protect from direct sun light.

QUALITY ASSURANCE

Krishna manufactures entire range of construction chemicals under compliance of ISO 9001-2000.

TECHNICAL SERVICES

While new advances and changes will take place one thing will never change is quality and meeting special needs of customer We are eager to work with you in development of new product and solve your problem.