

JAIFIX TA STD **CERAMIC TILE ADHESIVE**

BENEFITS :

- Prepacked factory controlled ensures consistent quality.
- Excellent adhesion - hence can be used tile on tile.
- Excellent waterproofing characteristics.
- Easy to use.

PRODUCT:

Prepacked Cementations tile adhesive which ensures excellent bond on concrete, plastered and even on ceramic and mosaic tile surfaces. JAIFIX TA STD ensures perfect watertightness.

PACKING & COVERAGE:

25 kg HDPE bag. 25 kg of JAIFIX TA STD will cover 5 to 8 m² with recommended thickness 3 to 4 mm.

DESCRIPTION:

JAIFIX TA STD is a adhesive for the permanent fixing of ceramic tiles both in damp and submerged conditions. JAIFIX TA STD can also be used for fixing tile on tile.

SURFACE PREPRATION:

All surfaces must be sound and thoroughly cleaned before JAIFIX TA STD is applied. All traces of greases or oil must be removed with KC Degreaser. All loose particles of mortar and points must be physically removed.

SURFACE:

JAIFIX TA STD can be applied directly on concrete, cement screeds, cement, lime mortars and existing tiles.

MIXING:

JAIFIX TA STD should be mixed with water in the ratio of 3:1 by volume. Water can be reduced or increased slightly to increase required consistency. A slow speed drill fitted with a suitable mixing paddle is recommended. Hand mixing may be allowed if drill/paddle is not available.

FINISHING:

Remove excess adhesive with a damp cloth before material has set.
Joint grouting may be commenced 24 hours after tiles have been laid.

SHELF LIFE:

JAIFIX TA STD is non-toxic. However, splashes on the skin should be washed well with water and in contact with eye occurs, wash well with water and seek medical advice.

TECHNICAL SERVICE:

While new advances and changes will take place one thing will never change is quality and meeting special needs of customer We are eager to work with you in development of new product and solve your problem.

