

K PUTTY

A READY TO USE ACRYLIC POLYMER BASED WALL PUTTY

DESCRIPTION

K PUTTY is an acrylic polymer based ready to use wall putty. Suitable for use on both pre-cast and conventional building areas on new internal surfaces of pre-cast concrete.

USES

Suitable for use pre-cast concrete, sand cement plaster, level brick work and block work, exposed concrete, plywood, AC sheets, Gypsum boards etc. the material can also be applied for redecoration on firm, old painted areas.

ADVANTAGES

- Ready to. Use.
- Excellent thixotropiness.
- Excellent adhesion.
- Ensures use of on all common types of building interiors.
- Easy to apply.
- Excellent finishing.
- No curing is required.
- Cutting is easily done using emery paper and involves no strain.
- Excellent consistency suitable for application.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION :

Remove all loose material by using Emery paper No. 180 and wiping of the powder with a cloth or a cotton waste.

APPLICATION

Apply **K PUTTY** using painter's putty knife or a mason's steel trowel apply the material on the surface. Allow to dry for 4 hours and rub the surface with emery paper No. 320. The loose powder on the surface is to be wiped with a cloth or cotton waste. After the material has dried apply a thin second coat (generally both coat do not exceed 2mm) and allow the material to dry. The drying time of each coat should be 4 hours, but will vary from surface to surface.

Finishing : Make sure that the material has fully covered the substrate and dried. Using 0 number sand paper ensure that the paper is fine and does not cause scratches on the **K PUTTY** coating area. After papering the entire area to the desired smoothness and finish, dust with a dry clean cloth to wipe off any powder on the surface due to papering. The **K PUTTY** area is now ready for painting.

Painting : The smooth surface finished with **K PUTTY** does not require any putty or primer before paint application. Just apply any paint as per the manufacturer's standard specification. Intact painting can commence within a few hours of **K PUTTY**.

PACKING & COVERAGE

K PUTTY is available in 1, 5, 10 & 20 Kg. plastic bucket. Coverage of approx 0.75 m² per kg when applied at thickness of 1 mm. (Depends upon the surface)

STORAGE

12 months storage life when stored in original unopened bags at between 5 and 45°C in a dry and shaded place.

HEALTH & SAFETY

K PUTTY is non-hazardous. It should not be swallowed or allowed to come into contact with skin or eyes. Suitable protective goggles and gloves should be worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical attention immediately, do not induce vomiting.

NOTE

All information is given in good faith on the results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since we don't have any control on site conditions and its uses.